Lloyd

Mercedes-Benz Unimog U300

Price available on Application

Condition: Used **Branch:** Newcastle

KEY FEATURES

- 3-way tipper
- Pick-up hitch
- Good all-round condition
- A52 Differential lock at front axle
- B42 dual line trailer brakes
- C87 Vertical exhaust pipe
- D11 Implement mounting plate DIN76060 type B, cat. 3
- D50 Rear mounting brackets
- E37 Permanent power socket 12V/15A, C3 impulse incl.
- E40 Electric trailer plug-in socket for ABS
- E42 Additional trailer plug-in socket, 12V, 13 poles
- E45 Front plug-in socket 24V, 7 poles
- E47 24 V equipment socket (40 A) with C-3 signal
- E54 Preparation two way radio 12V analogical
- E55 Radio preparation (wiring, antenna, etc.)
- F16 Preparation of cabin for mowing door/seat, right
- F60 Tilting device for cab
- G20 Additional gearbox with working gear range
- H08 Dual circuit hydraulic system proportional
- H14 Hydraulic system 4 valves
- H51 Hydraulic connection rear, 2 lines at valve 1

PRODUCT DETAILS

Type: Mercedes-Benz Unimog

Make: Mercedes-Benz

Model: Unimog 300

Registration Number: BA02 AGU

Stock Number: 2002

CONTACT DETAILS

Branch: Newcastle

Phone: 0191 267 7555

- H58 Pressure line rear hydr. circuit 2
- H59 Separate return line, rear
- H61 Snow plough relief
- H65 VarioPower (power hydraulic), closed+open circuit
- H68 Hydraul. pressure+sep.return line, middle, circ.2
- H75 Hydraulic connection front, 4 lines at valve 1+2
- H76 Hydraulic connection front, 4 lines at valve 3+4
- H78 Pressure line front for 2. hydr. circuit
- H79 Separate front return flow line
- H94 Front pressure and return line, hydraulic circuit 3+4
- H97 Carbon-acid-ester for hydr. system
- J08 Socket 24V in cab, C3 impulse included
- J24 Tachograph, 2 drivers, not EC
- J29 Adjustment/label for different sized tyres
- L45 Working lights rear, at cab
- L47 Add.raised headlights for front-mounted implements
- L51 Rotating beacon yellow,left & right, with supports
- N05 Engine power take-off, to rear, with flange
- N08 Live PTO incl. PTO front
- N09 PTO rpm limiter
- P25 Platform 2400 x 2050 x 400 mm
- Q29 Trailer hitch (38 mm pin)
- R27 Disc Wheels 11x20 super
- S07 Air-suspended contoured driver seat, heated
- S26 Windscreen elec. heatable, multi-layer glass
- S49 Rear window, sliding from left side
- S50 First-aid kit
- S82 Heated wide-angle mirror
- S83 ramp mirror

- X20 GVW Level increased
- X70 Warning stripes red/white, retroreflective
- Y46 Warning triangle and torch
- Z01 Left hand drive